



TECHNICAL DATA SHEET

PREMIUM DEXRON III / MERCON AUTOMATIC TRANSMISSION FLUID

Product Description:

OBLube Dexron III / Mercon ATF is a premium quality product which is formulated to meet the latest General Motors Dexron III, Ford Mercon, and Allison C4 fluid requirements. It is made from highly refined high viscosity index basestocks and specially blended with carefully balanced additives to meet the stringent requirements of a Dexron III / Mercon ATF.

Benefits:

OBLube Dexron III / Mercon ATF provides:

- Protection at low temperature start-up and operation required of a Dexron III fluid
- Excellent oxidative and thermal stability
- Excellent anti-rust properties
- Excellent anti-foaming and air release properties
- Excellent resistance to sludge formation
- Compatibility with wet clutches and automatic transmission components and materials.

Applications:

OBLube Dexron III / Mercon ATF can be used on :

- Passenger Car Automatic Transmissions requiring a Dexron or Mercon ATF specification
- Heavy Duty Power Trains and Transmissions requiring an Allison C4 fluid
- Power Steering Units
- Hydraulic Units requiring an ISO VG 32 or 46 fluid.

Performance Levels:

- General Motors Dexron IIIIG
- Ford Mercon
- Allison C4
- ZF TE ML 14
- MB 236.9
- Voith G-607
- Volvo S6-66

Typical Physical Characteristics:

| OBLUBE PREMIUM DEXRON III / MERCON AUTOMATIC TRANSMISSION FLUID | | | |
|---|------|-------------|--------------|
| Properties | Unit | Test Method | |
| Appearance | | Visual | Clear Liquid |
| Color | | Visual | Red |
| Density @ 15°C | kg/L | ASTM D 4052 | 0.872 |
| Viscosity @ 40°C | cSt | ASTM D 445 | 34.0 |
| Viscosity Index | | ASTM D 2770 | 160 |
| Flash Point | °C | ASTM D 92 | 180 (min.) |

Health and Safety:

OBLUBE Lubricants are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained. Use gloves which are impervious to oil and chemicals when handling used oils. Avoid skin contact. If lubricants come in contact with skin, wash immediately with soap and water.

Assawayer Trading Co. Ltd.,

P. O. Box 11309
Jubail Industrial City 31961
Kingdom of Saudi Arabia.
Tel: (03) 341-2125
Fax: (03) 341-7209