



أوبلي لوب
OBLUBE

TECHNICAL DATA SHEET

OBLUBE ULTRA HIGH PERFORMANCE ENGINE OIL

Product Description:

OBLube Ultra High Performance Engine Oil is a special multi-grade engine oil formulated from a special blend of selected high viscosity index mineral oils & race-proven additive technology for use in gasoline and diesel engines of passenger cars & light trucks operating under severe conditions. It uses a high quality Viscosity Index Improver which lets this excellent product stay-in-grade. This product is optimized to provide complete engine protection by lowering oil consumption, and having higher thermal stability and wider operating temperature performance.

Benefits:

OBLube Ultra High Performance Engine Oil provides:

- Low and High Temperature Engine Protection
- Prevention of Deposits in Piston Rings and Grooves
- Resists Sludge Formation & TBN Depletion
- Reduction of Oil and Fuel Consumption
- Trouble-free Operation in Severe Service
- An Excellent Crankcase Lubricant for Mixed-Fleet Operations

Performance Levels:

OBLube Ultra High Performance Engine Oil meets and exceeds the following approvals and specifications:

- API SL / CF
- ACEA-A-3-02/B3-98 # 2
- MB.229.1
- Volkswagen 505.00 (SAE 10W-40)
- VW 501.00 quality

Applications:

OBLube Ultra High Performance Engine Oil is applicable to:

- Passenger Cars and Light Trucks with Naturally Aspirated or Turbo-charged Petrol and Diesel Engines
- Commercial Road Vehicles
- Off High Way Vehicles and Equipment
- Agricultural Vehicles and Equipment
- Mixed-Fleet Requirements

Physical Characteristics:

OBLUBE ULTRA HIGH PERFORMANCE ENGINE OIL			
Properties	Test Method	Units	SAE 10W-40 / API SL/CF
Specific Gravity @ 30 °C	ASTM D1298		0.88
Viscosity @ 40 °C	ASTM D445	cSt	104.0
Viscosity @ 100 °C	ASTM D445	cSt	14.1
Viscosity Index	ASTM D2770		138
Pour Point	ASTM D97	°C	- 27
Cold Cranking Simulator @ -25°C	ASTM D5293	cP	6,600
High Temperature High Shear Viscosity	ASTM D4683	cP	3.81 @ 150°C
Total Base Number	ASTM D2896	mg KOH / g of oil	6.9
Phosphorus Content	ICP / AAS	%	0.14
Zinc Content	ICP / AAS	%	0.16

Health and Safety:

OBLUBE Lubricants are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained. Use gloves which are impervious to oil and chemicals when handling used oils. Avoid skin contact. If lubricants come in contact with skin, wash immediately with soap and water.

Assawayer Trading Co. Ltd.,

P. O. Box 11309
Jubail Industrial City 31961
Kingdom of Saudi Arabia.
Tel: (03) 341-2125
Fax: (03) 341-7209