

 Product name:
 Omega 58
 Page:
 1/9

 Supersedes date:
 2012-10-01
 Last revised date:
 2016-04-15

 Product No.:
 SDS-ID:
 GB-EN/6.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

<u>Product name:</u> Omega 58

Container size: 400 g, 5 kg & 15 kg

1.2. Relevant identified uses of the substance or mixture and uses advised against

<u>Application:</u> Lubricating grease.

1.3. Details of the supplier of the safety data sheet

Supplier: EU importer:

•

<u>Manufacturer</u> Ωmega Manufacturing Division

13th floor, Unit B, PAX Tower, 609 Eonju-ro

Gangnam-Gu, Seoul Korea 06108 Tel:+82-2-2088-3560 Fax:+82-2-513-3567

Further information can be

magna@magnagroup.com

obtained from:

1.4. Emergency telephone number

Emergency telephone: Call a Poison Center, emergency number or doctor/physician.

Product name:Omega 58Page:2/9Supersedes date:2012-10-01Last revised date:2016-04-15Product No.:SDS-ID:GB-EN/6.0

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP: Aquatic Chronic 3;H412Eye Irrit. 2;H319

STOT RE 2;H373 Aquatic Chronic 2;H411

2.2. Label elements



Warning

Contains: Benzoic acid

H319 Causes serious eye irritation.

H373N May cause damage to organs (lungs) through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

P260 Do not breathe vapours.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P273 Avoid release to the environment.

P501 Dispose of contents/container as hazardous waste.

2.3. Other hazards

Other: Prolonged or repeated contact with skin may cause redness, itching, irritation and

eczema/chapping. The harmful effects may increase in used grease.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

The product contains: white mineral oil, fillers and additives . ${\sf DMSO\text{-}content} < 3\%$

CLP:

<u>%:</u>	CAS-No.:	EC No.:	REACH Reg. No:	Chemical name:	Hazard classification:	Notes:
1-5	65-85-0	200-618-2	01-2119455536-33-	Benzoic acid	STOT RE 1;H372Na Skin Irrit. 2;H315 Eye Dam. 1;H318	
1-5	13463-67-7	236-675-5	01-2119489379-17-	Titanium dioxide	-	#
0.1-1	110-25-8	203-749-3	01-2119488991-20-	(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	Acute Tox. 4;H332 Skin Irrit. 2;H315 Eye Dam. 1;H318 Aquatic Acute 1;H400	
0,1-1	95-38-5	202-414-9	01-2119777867-13-	2-(2-Heptadec-8-enyl-2- imidazolin-1-yl)ethanol	Acute Tox. 4;H302 Skin Corr. 1C;H314 Eye Dam. 1;H318 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	

Notes: #: The substance has been assigned an exposure limit.

 Product name:
 Omega 58
 Page:
 3/9

 Supersedes date:
 2012-10-01
 Last revised date:
 2016-04-15

 Product No.:
 SDS-ID:
 GB-EN/6.0

References: The full text for all hazard statements is displayed in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Move into fresh air and keep at rest. In case of persistent throat irritation or

coughing: Seek medical attention and bring these instructions.

Skin contact: Remove contaminated clothing immediately and wash skin with soap and water.

In case of rashes, wounds or other skin disorders: Seek medical attention and

bring along these instructions.

Eve contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact

lenses and open eyelids widely. If irritation persists: Seek medical attention and

bring along these instructions.

<u>Ingestion:</u> Immediately rinse mouth and drink plenty of water. Keep person under

observation. If person becomes uncomfortable seek hospital and bring these

instructions.

4.2. Most important symptoms and effects, both acute and delayed

<u>Symptoms/effects:</u> See section 11 for more detailed information on health effects and symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Small fires: Extinguish with carbon dioxide or dry powder.

Larger fires: Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

<u>Specific hazards:</u> During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective equipment for fire-

Selection of respiratory protection for fire fighting: follow the general fire

precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Avoid contact with skin and eyes. Follow precautions for safe handling described

in this safety data sheet.

6.2. Environmental precautions

Environmental Do not discharge into drains, water courses or onto the ground.

precautions:

fighters:

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Absorb spillage with oil-absorbing material. Clean contaminated area with oil-

removing material.

6.4. Reference to other sections

<u>References:</u> For personal protection, see section 8.

For waste disposal, see section 13.

Product name:Omega 58Page:4/9Supersedes date:2012-10-01Last revised date:2016-04-15Product No.:SDS-ID:GB-EN/6.0

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice: Observe good chemical hygiene practices. Avoid prolonged and repeated contact

with grease, particularly used grease. Always remove grease with soap and

water or skin cleaning agent, never use organic solvents.

<u>Technical measures:</u> Work practice should minimise contact.

<u>Technical precautions:</u> When working with heated grease, mechanical ventilation may be required.

7.2. Conditions for safe storage, including any incompatibilities

<u>Technical measures for safe</u> No special precautions.

storage:

Storage conditions: Store in tightly closed original container.

7.3. Specific end use(s)

Specific use(s): Lubricant.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

CAS-No.:	Chemical name:	As:	Exposure limits:	Type:	Notes:	References:
13463-67-7	Titanium dioxide, total inhalable dust	-	10 mg/m3	TWA	-	EH40
13463-67-7	Titanium dioxide, respirable dust	-	4 mg/m3	TWA	-	EH40

8.2. Exposure controls

Engineering measures: Provide adequate ventilation. When working with heated grease, mechanical

ventilation may be required. Provide access to washing facilities incl. soap,

skin cleanser and fatty cream.

<u>Personal protection:</u> Personal protection equipment should be chosen according to the CEN

standards and in discussion with the supplier of the personal protective

equipment.

Respiratory equipment: In case of inadequate ventilation use suitable respirator. Use respiratory

equipment with particle filter, type P2.

<u>Hand protection:</u> Risk of contact: Wear protective gloves. Nitrile gloves are recommended.

Other types of gloves can be recommended by the glove supplier.

Eve protection: Risk of contact: Wear goggles/face shield.

<u>Hygiene measures:</u> Wash hands after handling. Change contaminated clothing.

Environmental Exposure

Controls:

Not available.

Product name:Omega 58Page:5/9Supersedes date:2012-10-01Last revised date:2016-04-15

Product No.: SDS-ID: GB-EN/6.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance: Grease.

Colour: White.

Odour: Mild.

pH: Not applicable.

Boiling point: > 300 °C

Flash point: > 200 °C

Evaporation rate: Not available.

Explosive limits Not available.

<u>Vapour pressure:</u> < 0,01 mmHg (20 °C)

Relative density: 0,88

Solubility: Immiscible with water.

<u>Decomposition</u> Not available.

temperature (°C):

<u>Viscosity:</u> Not applicable.

9.2. Other information

Other data: Not available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: Not reactive.

10.2. Chemical stability

<u>Stability:</u> Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions: None known.

10.4. Conditions to avoid

Conditions to avoid None specific.

10.5. Incompatible materials

<u>Incompatible materials:</u> Strong oxidising substances.

10.6. Hazardous decomposition products

Hazardous decomposition

products:

None known.

Product name: Omega 58 Page: 6/9 2012-10-01 2016-04-15 Supersedes date: Last revised date:

Product No.: SDS-ID: GB-EN/6.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute Toxicity (Oral): Based on available data, the classification criteria are not met. Acute Toxicity (Dermal): Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Acute Toxicity (Inhalation): Based on available data, the classification criteria are not met. Skin Corrosion/Irritation:

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin

sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive Toxicity: Based on available data, the classification criteria are not met.

STOT - Single exposure: Based on available data, the classification criteria are not met.

May cause damage to organs (lungs) through prolonged or repeated exposure. STOT - Repeated exposure:

Aspiration hazard: Based on available data, the classification criteria are not met.

Inhalation of oil mist or vapours formed during heating of the product will irritate Inhalation:

the respiratory system and provoke coughing.

Degreasing. Prolonged or repeated contact with skin may cause redness, itching, Skin contact:

irritation and eczema/chapping.

Direct contact may irritate. Eve contact:

Ingestion: May irritate and cause malaise.

Prolonged or repeated contact with used grease may cause serious skin Specific effects:

diseases, such as dermatitis. The harmful effects may increase in used grease.

 Product name:
 Omega 58
 Page:
 7/9

 Supersedes date:
 2012-10-01
 Last revised date:
 2016-04-15

 Product No.:
 SDS-ID:
 GB-EN/6.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity: The product is toxic to aquatic organisms, may cause long-term adverse effects

in the aquatic environment.

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine

M-factor (acute): 1

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol

M-factor (acute): 1 M-factor (chronic): 10

12.2. Persistence and degradability

<u>Degradability:</u> The product is expected to be slowly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT/vPvB: No data available.

12.6. Other adverse effects

Other adverse effects: None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 20 01 26

Product name: Omega 58 Page: 8/9 Supersedes date: 2012-10-01 2016-04-15 Last revised date: Product No.: SDS-ID: GB-EN/6.0

SECTION 14: TRANSPORT INFORMATION

The product is covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN-No: 3077

14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Benzoic Proper Shipping Name:

14.3. Transport hazard class(es)

Class: 9

14.4. Packing group

Ш PG:

14.5. Environmental hazards

Environmentally Hazardous

substance:

14.6. Special precautions for user

Special precautions: None known.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk: Not known.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments 2008 No. 2852 - The REACH Enforcement Regulations National regulation:

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, with amendments.

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No.

2677) with amendments.

EH40/2005, Workplace exposure limits 2005, with amendments.

The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

15.2. Chemical Safety Assessment

CSA status: No information available.

 Product name:
 Omega 58
 Page:
 9/9

 Supersedes date:
 2012-10-01
 Last revised date:
 2016-04-15

 Product No.:
 SDS-ID:
 GB-EN/6.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 1-16.

Omega Manufacturing Division

13th floor, Unit B, PAX Tower, 609 Eonju-ro,

Gangnam-Gu, Seoul, Korea 06108

Tel: +82-2-2088-3560 Fax: +82-2-513-3567

Web site: www.magnagroup.com

The Omega Trade Mark is the property of ITW, Inc., and is used under license by ITW PP & F Korea Limited.

Additional information: Classification according to Regulation (EC) No. 1272/2008: Calculation method.

Wording of H-statements:

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H372Na Causes damage to organs (lungs) through prolonged or repeated exposure if

inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.